

OUTDOOR ACCESS POINT

QN-O-240



Up to 3 Gbps
Data Rate



2.5 GbE
Connectivity



2.4 GHz - 2x2,
5 GHz - 2x2



MU-MIMO
With OFDMA



1 Year
Warranty

PRODUCT OVERVIEW

QN-O-240 built-in with a smart antenna and MU-MIMO technology provides high data-rates even in high-density and high-interference environments.

QN-O-240 provides concurrent dual-band, 802.11ax wireless networking solutions. OFDMA technology provides highly efficient fast speed, awesome coverage and smooth performance in high-density areas like railway stations, hospitals, malls, public places, universities etc.

QN-O-240 is manageable through a centralized platform and supported by Quantum Rudder. QN-O-240 can also be deployed as a standalone Access Point.

Each Access Point comes with a one-year limited liability manufacturer's warranty from the date of activation and theft prevention functionality to protect assets from misuse.

KEY FEATURES

- **Delivering high-performance outdoor Wi-Fi access.**
Deploy secure and reliable outdoor hotspots at Transportation hubs, Stadiums, Smart cities and Rural Wi-Fi setups.
- **Phenomenal Wi-Fi performance.**
Engineered for phenomenal Wi-Fi performance even in high-density environments for demanding voice and video applications. Provides improved coverage, increased capacity and seamless performance in dense environments.
- **Cost-Efficient Connectivity.**
Reduces operational costs and the expense of additional hardware required for deployment by service providers/telcos. SFP port provides high-speed fiber backhaul without any additional hardware.
- **Theft prevention functionality.**
Access Point is locked for deployment in any other network until decommissioned from the existing network.
- **Industrial-grade IP67 enclosure.**
IP67 rating can withstand challenging environments with extreme temperatures and dusty environments.
- **Easy to manage.**
Easily manage Wi-Fi infrastructure through the feature-rich Quantum Rudder management console.

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax
	2.4 GHz	IEEE 802.11b/g/n/ax
Operating Mode	Access point, Router, Mesh mode	
Networking Mode	IPv4, IPv6, IPv4v6 (Dual stack), Gateway mode(NAT), Bridge mode	
Maximum Data Rates	5 GHz	802.11ax@ 160 MHz:2400 Mbps
		802.11ax@ 80 MHz:1201 Mbps
		802.11ax@ 40 MHz: 600 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11ac@ 80 MHz: 1083.3 Mbps
		802.11ac@ 40 MHz: 500 Mbps
		802.11ac@ 20 MHz: 240.5 Mbps
	2.4 GHz	802.11ax@ 40 MHz: 600 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11n@ 40 MHz: 500 Mbps
		802.11a/g@ 20 MHz: 54 Mbps
		802.11b@ 20 MHz: 11 Mbps
Maximum Receiver Sensitivity	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Supported Channels	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
		Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
Modulation Schemes	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11b	BPSK, QPSK, CCK
Radio Chains and Spatial Streams	2x2:2	Streams in 5GHz-OFDMA with MU-MIMO
	2x2:2	Streams in 2.4GHz- OFDMA with MU-MIMO
Channel Size	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80 (VHT) MHz
	802.11ax	20/40/80/160 (HE) MHz
Wireless Security	WPA3-AES personal, Enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed- AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	
	WEP-64, WEP-128,	
	MAC-based authentication	
	Captive portal based authentication	

Wireless Security	802.11i	
	Quantum SECURE	
	Hide SSID in beacons	
WIPS/WIDS for Various Attack Signatures	Rogue Station Detection	
	Deauth attack detection, RTS and CTS abuse attack detection	
	Assoc attack detection, Fata jack tool detection,	
	DHCP snooping server detection, Honeypot / Evil Twin attacks detection	
	Misconfigured AP detection	
	SSH Brute force attacks detection, Man in the middle attacks detection	
	Port scanning detection, Ad-Hoc connection detection, Password guessing attacks detection	
External DB Support	Radius, Active directory, LDAP	
Web Authentication	QN-Secure+, RADIUS, Active directory, LDAP	
User Authentication	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
	Directory	QIM, Microsoft active directory, LDAP, G suite, Oauth
	Mode	Via Controller / Access points
Roaming	IEEE 802.11k (Assisted Roaming)	
	IEEE 802.11v (BSS Transition Management)	
	IEEE 802.11r (Fast BSS Transition (FT))	
	Pairwise Master Key (PMK) caching	
	Opportunistic key caching	
	Seamless roaming for captive portal users	
Channel / Tx Power Management	Auto / Manual channel selection	
	Speedy channel for performance optimization	
	Channel switch for performance optimization	
	ATP-Automatic Transmit Power management	
Client Management	Band steering	
	Band balancing	
	Airtime fairness	
Guest Management	WISPr – Captive portal, HotSpot 2.0	
Native Guest Portal	Customized Template	Yes (User define, Theme-based)
	Authentication Method	Click-through, Access code, Self-sign-up (SMS, Email), Sponsor based (Domain-based, Individual Email ID based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota based

Diagnostics	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, PCAP capture (Wired and Wireless), ARP scanner
Access Control List	Force DHCP
	URL & Application filtering
	Full Client Isolation, Deny inter-user bridging, Deny intra-VLAN traffic
	Bandwidth Restriction per SSID/User
	OS restriction
	L2 (MAC) filtering
	L3 (IP) / L4 (Port) filtering
	MAX clients per radio
	Internet freeze per SSID/user
Meshing	Wireless (singlehop / multihop)
	Wired
Radio Management	DTIM interval
	OFDM Only (Disables 802.11b)
	BSS Rate and management rate
	UAPSD (Power save)
	Inactivity timeout
Network Management	IEEE 802.11d/h (DFS) support
	LLDP discovery, SFlow
	Proxy ARP
	DHCP options 60 and 82
	Port forwarding in router mode
Administration	WLAN scheduling
	Internet speed test
	Schedule reboot
Wi-Fi 6 Features	Target wake time
	BSS colouring
	Spatial reuse
	Orthogonal frequency division multiple access (OFDMA)
	Preamble puncturing
Advance Features	Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
	Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas
	Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz
	Space-time block coding (STBC) for increased range and improved reception
	Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
	Transmit beam-forming (TxBF) for increased signal reliability and range

Networking						
Ethernet WAN	WAN (DHCP/Static/PPPoE)					
Protocols	Static, RIP v2, OSPF v2					
Tunneling	GRE, IPSec, Wire guard, OVPN					
Multi- WAN	Yes, Auto-Failover					
DHCP Server	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy					
WAN Security	Ethernet port block management					
PPP Interface	PPPoE, L2TP, L2TP with IPSec					
DNS	Static, Caching, Dynamic DNS					
NAT	Masquerade (SNAT), Port forwarding (DNAT)					
VLAN Support	802.1Q (1 per BSSID or dynamic per user-based on RADIUS), Port-based (Tagged, untagged)					
Quality of Service						
Auto-QoS, 802.11e,						
Manual QoS (DSCP based, Voice, Video, BE and BK)						
WMM						
802.1p						
Performance & Capacity						
Peak PHY Rates	5 GHz	2400 Mbps (802.11ax)				
	2.4 GHz	600 Mbps (802.11ax)				
Client Capacity	Up to 512 clients per Access point					
SSID	Up to 16 per access point (8 per Radio)					
RF		QN-O-240	QN-O-240-N			
			QN-ANT-5-5DB / QN-ANT-2-5DB	QN-ANT-5-8DB / QN-ANT-2-8DB	QN-ANT-5-12DB/ QN-ANT-2-12DB	QN-ANT-5-15DB/ QN-ANT-2-15DB
Maximum Aggregate Transmit Power (As per country regulations)	5 GHz	26 dBm	26 dBm	24 dBm	24 dBm	24 dBm
	2.4 GHz	27 dBm	27 dBm	25 dBm	25 dBm	25 dBm
Antenna Gain (Max)	5 GHz	6 dBi	5 dBi	8 dBi	12 dBi	15 dBi
	2.4 GHz	6 dBi	5 dBi	8 dBi	12 dBi	15 dBi
EIRP (As per country regulations)	5 GHz	32 dBm	31 dBm	32 dBm	36 dBm	39 dBm
	2.4 GHz	33 dBm	32 dBm	33 dBm	37 dBm	40dBm
Antenna Type		Built-in integrated antenna for both radios	External antennas connectors			

Power		
Rating	802.3 af PoE / at PoE+ (Class 4) (Fully functional with all components)	
Physical Interfaces	QN-O-240	QN-O-240-N
Ethernet	WAN/LAN: 1 x 10/100/1000/2.5G Base-T Ethernet, Auto-MDIX, RJ-45 with 802.3at PoE	
	802.3bz specifications, 802.3az Energy Efficient Ethernet (EEE)	
Fiber	WAN/LAN : 1 x 1 G Base-X (SX / LX) SFP port	
Buttons	Restart/Reset	
LED Indicators	Power, 2.4 GHz , 5 GHz , Uplink	
Management		
Device Management	Standalone, Local (web UI), SSH (CLI)	
	Quantum Rudder (Controller based)	
	Quantum Rudder (On-premises VM)	
	Quantum Rudder appliances (RR-200, RR-300, RR400)	
	Through NMS using SNMP MIBs	
	Local device web management	
Device /System Monitoring	SNMP v1, v2c, v3, Syslog	
Controller DR (Disaster Recovery)	Supported	
Device Security		
Certificate	Locally-significant certificates using PKI	
Controller Communication	Encrypted	
Port Access	802.1x RADIUS supplicant	
Application Integration		
PM WANI,		
NMS Integration - ZABBIX, PRTG Monitor, Open NMS		
Environmental		
Operating temperature	-40°C (-40F) ~ +70°C (+158F)	
Humidity	5% ~ 100% Non-Condensing	
Wind Resistance	160 kmph for sustained wind, 250 kmph for wind gusts	
Standard	IP67	
Physical		
Dimensions	23.9cm(L), 19.5cm(W), 8.3cm(H)	
Weight	1575 g (3.47 lbs)	
Mounting kit	Pole mount	
Firmware Management		
Cloud-managed firmware update		
Scheduled firmware and security update		
Firmware upgrade via Access Point local GUI		

Certifications	
Regulatory	FCC
	ETA
	BIS
Environmental	RoHS
	CE
	IP67

ORDERING INFORMATION

Part Code	Description
QN-O-240	Quantum QN-O-240 dual-band 802.11 ax outdoor wireless access point with 1x2.5G Eth PoE in and 1x1G SFP port, 2x2:2 streams with 1 year warranty
QN-O-240-N	Quantum QN-O-240-N dual-band 802.11 ax outdoor wireless access point with 1x2.5G Eth PoE in and 1x1G SFP port, 2x2:2 streams, connectorized external antennas with 1 year warranty.
Accessories Part Code	Description
QN-ANT-2-5DB	2.4GHz External Outdoor Antennae with N-Connector, Gain: 5dBi
QN-ANT-2-8DB	2.4GHz External Outdoor Antennae with N-Connector, Gain: 8dBi
QN-ANT-2-12DB	2.4GHz External Outdoor Antennae with N-Connector, Gain: 12dBi
QN-ANT-2-15DB	2.4GHz External Outdoor Antennae with N-Connector, Gain: 15dBi
QN-ANT-5-5DB	5GHz External Outdoor Antennae with N-Connector, Gain: 5dBi
QN-ANT-5-8DB	5GHz External Outdoor Antennae with N-Connector, Gain: 8dBi
QN-ANT-5-12DB	5GHz External Outdoor Antennae with N-Connector, Gain: 12dBi
QN-ANT-5-15DB	5GHz External Outdoor Antennae with N-Connector, Gain: 15dBi