

INROOM ACCESS POINT

QN-H-240



Up to 3 Gbps
Data Rate



1 GbE
Connectivity



2.4 GHz - 2x2,
5 GHz - 2x2



MU-MIMO
With OFDMA



3 Years
Warranty

PRODUCT OVERVIEW

Introducing the QN-H-240 Room Access Point, a dual-band Wi-Fi 6 solution from Quantum Networks, designed to transform connectivity in educational and business spaces. With speeds of up to 3 Gbps, it delivers exceptional performance for modern networking needs.

Ideal for small to medium-sized rooms for hotels or residences, the QN-H-240 ensures seamless, high-speed internet access. It is perfect for supporting both modern and legacy devices, making it a versatile choice for diverse setups. Enjoy effortless wall mounting and simple remote monitoring via Quantum Rudder. Step into the Quantum era with the QN-H-240 Room Access Point with WPA3 security, a game-changer in connectivity from Quantum Networks.

KEY FEATURES

Loaded with Cutting-Edge 802.11ax Technology

The QN-H-240 dual-band Wi-Fi 6 Access Point, featuring advanced 802.11ax technology, combines compact design and small form factor, making it a perfect fit for small to medium-sized hotel and residences. Equipped with WPA3 security, it ensures a secure and reliable network.

Exceptional Wi-Fi Performance

Designed with a wall-mountable and space-saving form factor, the QN-H-240 offers seamless Wi-Fi 6 performance with 160 MHz channel support. It delivers speeds of up to 3 Gbps, ideal for educational institutions, businesses, and residential setups, providing reliable connectivity to meet modern networking demands.

Comprehensive All-in-One Solution

The QN-H-240 supports both modern and legacy devices, making it a versatile, future-ready solution for diverse networking needs. Its dual-band 2.4/5 GHz radios and dual MU-MIMO spatial streams ensure exceptional performance, whether for business-critical applications or residential users.

Diverse Service Support

The QN-H-240 excels in environments requiring high device density, offering simultaneous connections without compromising speed or reliability. Perfect for educational institutions, businesses, and hospitality markets, it is tailored to meet the growing demand for efficient and compact wireless solutions.

Step into the Quantum era with the QN-H-240, a cutting-edge, small-form-factor Wi-Fi 6 access point.

TECHNICAL SPECIFICATIONS

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax
	2.4 GHz	IEEE 802.11b/g/n/ax
Operating Mode	Access point	
Networking Mode	Bridge mode	
Maximum Data Rates	5 GHz	802.11ax@ 160 MHz: 2402 Mbps
		802.11ax@ 80 MHz: 2402 Mbps
		802.11ax@ 40 MHz: 1147.1 Mbps
		802.11ax@ 20 MHz: 573.5 Mbps
		802.11ac@ 80 MHz: 2166.7 Mbps
		802.11ac@ 40 MHz: 1000 Mbps
	2.4 GHz	802.11ac@ 20 MHz: 481.8 Mbps
		802.11ax@ 40 MHz: 573.5 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11n@ 40 MHz: 500 Mbps
		802.11a/g@ 20 MHz: 54 Mbps
		802.11b@ 20 MHz: 11 Mbps
Maximum Receiver Sensitivity	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Supported Channels	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
	Dynamic frequency selection (DFS) optimizes the use of available RF spectrum	
Channel Bands	5 GHz	5.15-5.25 GHz (U-NII-1), 5.25-5.35 GHz (U-NII-2A), 5.47-5.725 GHz (U-NII-2C), 5.725-5.85 GHz (U-NII-3) (As per country regulations)
	2.4 GHz	2.4-2.484GHz (ISM) (As per country regulations)
Modulation Schemes	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11b	BPSK, QPSK, CCK
Radio Chains and Spatial Streams	2x2:2	Streams in 5GHz-OFDMA with MU-MIMO
	2x2:2	Streams in 2.4GHz- OFDMA with MU-MIMO
Channel Size	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80/160 (VHT) MHz
	802.11ax	20/40/80/160 (HE) MHz
Wireless Security	WPA3-AES personal, Enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed-AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	

Wireless Security	WEP-64, WEP-128	
	802.11 w MFP (Management Frame Protection)	
	MAC-based authentication	
	Captive portal-based authentication	
	802.11i, Quantum Secure	
	Hide SSID in beacons	
External DB Support	Radius, Active directory, LDAP, TACACS+	
Web Authentication	QN-Secure+, RADIUS, Active directory, LDAP	
User Authentication	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
	Directory	QIM, Microsoft active directory, LDAP, G suite, Oauth
	Mode	Via Controller /Access points
Roaming	IEEE 802.11k (Assisted Roaming)	
	IEEE 802.11v (BSS Transition Management)	
	IEEE 802.11r (Fast BSS Transition (FT))	
	Pairwise Master Key (PMK) caching	
	Opportunistic key caching	
	Seamless roaming for captive portal users	
Channel / Tx Power Management	Auto / Manual channel selection	
	Speedy channel for RF optimization	
	Channel switch for RF optimization	
	ATP-Automatic Transmit Power management	
Client Management	Band steering	
	Band balancing	
	Airtime fairness	
Guest Management	WISPr – Captive portal	
Native Guest Portal	Customized Template	Yes (User define, Theme based)
	Authentication Method	Click-through, Access code, Self-sign-up (SMS, Email), Sponsor based (Domain-based, Individual Email ID based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota based
Access Control List	URL & Application filtering /Whitelisting	
	Full Client Isolation, Deny inter-user bridging, Deny intra-VLAN traffic	
	Bandwidth Restriction per SSID/User	
	OS restriction	
	L2 (MAC) filtering	
	L3 (IP) / L4 (Port) filtering	
	MAX clients per radio	
	Internet freeze per SSID/User	
	Session control	
Random MAC Detection		

Radio Management	DTIM interval
	OFDM Only (Disables 802.11b)
	BSS Rate and management rate
	UAPSD (Power save)
	Inactivity timeout
	Radio mode control
	RTS/CTS Threshold
WDS	Point to Point
	Point to MultiPoint
Network Management	IEEE 802.11d/h (DFS) support
	LLDP discovery
	Proxy ARP
	DHCP options 43, 60 and 82
	Port forwarding in router mode
Administration	WLAN scheduling
	Schedule reboot
Radius Integration	CoA (Change of Authorization)
	MAC Authentication
	Dynamic VLAN
Wi-Fi 6 Features	Target wake time
	BSS colouring
	Spatial reuse
	Orthogonal frequency division multiple access (OFDMA)
Advance Features	Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz
	Space-time block coding (STBC) for increased range and improved reception
	Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
	Transmit beam-forming (TxBF) for increased signal reliability and range
Networking	
Ethernet WAN	WAN (DHCP/Static/PPPoE)
Tunneling	IPSec
Multi-WAN	Yes, Auto-Failover
DHCP Server	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy
WAN Security	Ethernet port block management
PPP Interface	PPPoE
DNS	Static, Caching
NAT	Masquerade (SNAT), Port forwarding (DNAT)
VLAN Support	802.1Q (1 per BSSID), Port-based (Tagged, untagged)
Supported Features	Safe Search, ALG Control
	UPnP, DMZ Host, Adblock

Diagnostics		
Network Diagnostics	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, ARP scanner	
RF Diagnostics	PCAP capture, Airbender	
Quality of Service		
Auto-QoS, 802.11e,		
Manual QoS (DSCP based, Voice, Video, BE and BK)		
WMM, 802.1p		
WiFi Calling		
DiffServ		
Performance & Capacity		
Peak PHY Rates	5 GHz	2402 Mbps (802.11ax)
	2.4 GHz	573.5 Mbps (802.11ax)
Client Capacity	Up to 192 clients per access point	
SSID	Up to 16 per access point	
RF		
Maximum Aggregate Transmit Power (Adjusted as per country regulations)	5 GHz	21 dBm
	2.4 GHz	23 dBm
Antenna Type	Built-in integrated antenna for both radios	
Antenna Gain (Max)	5 GHz	3 dBi
Antenna Gain (Max)	2.4 GHz	3 dBi
EIRP	5 GHz	24 dBm
	2.4 GHz	26 dBm
Power		
Rating	802.3 af PoE /at PoE+(Class 4) (Fully functional with all components)	
Physical Interfaces		
Ethernet	WAN: 1 x 10/100/1000 Base-T ethernet, Auto-MDIX, RJ-45 with 802.3at PoE	
	LAN: 1 x 10/100/1000 Base-T ethernet	
	802.3az Energy Efficient Ethernet (EEE)	
Buttons	Restart/Reset	
LED indicators	Quick Setup, Cloud / Standalone	
Management		
Device Management	Standalone, Local (web UI), SSH (CLI)	
	Quantum Rudder	
Device /System monitoring	SNMP v1, v2c, v3, Syslog	
NTP Server Configuration	Supported	
Traffic Monitoring	IPDR Logs (IPFix , Netflow v9)	

Environmental	
Operating Temperature	-20°C (-4F) ~ +55°C (+131F)
Humidity	5% ~ 95% non-condensing
Standard	Plenum-rated (UL2043)

Physical	
Dimensions	8.5 cm (L), 8.5 cm (W), 4.5 cm (H)
Weight	0.26 kg (0.57 lbs)

Firmware Management	
Cloud-managed firmware update	
Firmware upgrade via Access Point local GUI	

Certifications and Compliances		
	Parameter	Standards
Regulatory (IN)	IPv6 Ready	
	ETA (WPC)	NABL 2.4, NABL 5
Environmental Compliances	CE	

ORDERING INFORMATION

Part Code	Description
QN-H-240	Quantum Networks QN-H-240 Dual-Band 802.11ax Wall Plate Wireless Access Point, 2X2:2 Streams, 1 X 1G Base-T Port (One 802.3af/at PoE In) & 1 X 1G Base-T Port (accessible behind the faceplate). Includes 3 Year Online Activation Warranty. Does not include PoE injector or power adaptor. Does not include cloud controller license.