INDOOR ACCESS POINT QN-I-270







Up to 1.7 Gbps Data Rate



2.5 GbE Connectivity



2.4 GHz - 2x2, 5 GHz - 2x2



MU-MIMO With OFDMA



3 Years Warranty

The increasing demands for Wi-Fi capacity in the Education, Enterprise sectors and medium-sized venues, fueled by the proliferation of connected devices, pose a significant challenge. Introducing the QN-I-270 Access Point equipped with the latest Wi-Fi 6 (802.11ax) technology. It offers an optimal combination of increased capacity, improved coverage and cost-effectiveness in densely populated environments.

PRODUCT OVERVIEW

The necessity for Wi-Fi coverage has become imperative across enterprises, educational institutions, medium-sized venues and smart cities. The QN-I-270 operates as a mid-range dual-band, dual-concurrent Access Point, supporting four spatial streams (2x2:2 in 2.4GHz/5GHz) and achieving peak data rates of up to 1774 Mbps.

Leveraging OFDMA technology, the QN-I-270 guarantees remarkably efficient high-speed connectivity, impressive coverage and seamless performance—all managed by Quantum Rudder.

Each access point includes a three-year limited liability manufacturer's warranty from the activation date and incorporates theft prevention functionality, safeguarding assets from potential misuse.

KEY FEATURES

Packed with the latest 802.11ax technology

The QN-I-270 is equipped with the latest advancements in 802.11ax technology, encompassing all the benefits of a high-efficiency 11ax Access Point. It supports key Wi-Fi 6 features, including OFDMA, Target Wake Time, BSS coloring and spatial reuse.

Efficient mesh networking

Reduce costly cabling and complex mesh configurations with QN Mesh wireless meshing technology.

Converged access point

The built-in BLE support along with the USB port, enable seamless integration of current and future wireless technologies.

Enhanced device connectivity

Simultaneously connect more devices with four MU-MIMO spatial streams and concurrent dual-band 2.4/5 GHz radios, while optimizing device performance.

QN-I-270 Wi-Fi 6 access point certified by Wi-Fi Alliance under Wi-Fi Certified 6.



Wi-Fi			
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax	
	2.4 GHz	IEEE 802.11b/g/n/ax	
Operating Mode	Access point, Router, Mesh mode		
Networking Mode	IPv4, IPv6, IPv4v6 (Dual stack), Gateway mode (NAT), Bridge mode		
		802.11ax@ 80 MHz:1201 Mbps	
		802.11ax@ 40 MHz: 573.5 Mbps	
	5 GHz	802.11ax@ 20 MHz: 286.8 Mbps	
	3 GHZ	802.11ac@ 80 MHz: 1083.3 Mbps	
		802.11ac@ 40 MHz: 500 Mbps	
Maximum Data Rates		802.11ac@ 20 MHz: 240.5 Mbps	
		802.11ax@ 40 MHz: 573.5Mbps	
		802.11ax@ 20 MHz: 286.8 Mbps	
	2.4 GHz	802.11n@ 40 MHz: 500 Mbps	
		802.11a/g@ 20 MHz: 54 Mbps	
		802.11b@ 20 MHz: 11 Mbps	
Maximum Receiver	5 GHz	-98 dBm	
Sensitivity	2.4 GHz	-93 dBm	
	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)	
Supported Channels	2.4 GHz	1-13 (As per country regulations)	
		Dynamic frequency selection (DFS) optimizes the use of available RF spectrum	
Channel Bands	5 GHz	5.15-5.25 GHz (U-NII-1), 5.25-5.35 GHz (U-NII-2A), 5.47-5.725 GHz (U-NII-2C), 5.725-5.85 GHz (U-NII-3) (As per country regulations)	
	2.4 GHz	2.4-2.484GHz (ISM) (As per country regulations)	
	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256- QAM, 1024-QAM	
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM	
Modulation Schemes	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM	
	802.11b	BPSK, QPSK, CCK	
Radio Chains and	2x2:2	Streams in 5GHz-OFDMA with MU-MIMO	
Spatial Streams	2x2:2	Streams in 2.4GHz- OFDMA with MU-MIMO	
	802.11n	20/40 (HT) MHz	
Channel Size	802.11ac	20/40/80 (VHT) MHz	
	802.11ax	20/40/80 (HE) MHz	
Wireless Security	WPA3-AES personal, enhanced open (OWE)		
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)		
	WPA3-WPA2 Mixed- AES personal, Open		
	WPA2-TKIP/AES personal, Open		
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)		



	WPA personal, WPA Mix	ked-Enterprise (802.1x/EAP-PEAP)
	WEP-64, WEP-128	
	802.11 w MFP (Management Frame Protection)	
Wireless Security	MAC based authenticat	ion, Captive portal-based authentication
	802.11i, Quantum Secure	
	Hide SSID in beacons	
External DB Support	Radius, Active directory	, LDAP, TACACS+
Web Authentication	QN-Secure+, RADIUS, Active directory, LDAP	
	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
User Authentication	Directory	QIM, Microsoft active directory, LDAP, Gsuite, Oauth
	Mode	Via Controller / Access points
	IEEE 802.11k (Assisted F	Roaming)
	IEEE 802.11v (BSS Trans	sition Management)
D	IEEE 802.11r (Fast BSS	Transition (FT))
Roaming	Pairwise Master Key (PN	MK) caching
	Opportunistic key caching	
	Seamless roaming for captive portal users	
	Auto / Manual channel selection	
Channel / Tx Power	Speedy channel for RF optimization	
Management	Channel switch for RF optimization	
	ATP-Automatic Transmit Power management	
	Band steering	
Client Management	Band balancing	
	Airtime fairness	
Guest Management	WISPr – Captive portal, HotSpot 2.0	
	Customized Template	Yes (User define, Theme based)
Native Guest Portal	Authentication	Click-through, Access code, Self-sign-up (SMS, Email),
	Method	Sponsor based (Domain-based, Individual Email ID based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota based
	Force DHCP	CARL SE LE CE
	URL & Application filtering / Whitelisting	
	Full Client Isolation, Deny inter user bridging, Deny intra VLAN traffic	
	Bandwidth Restriction per SSID/per User	
Access Control List	OS restriction	
	L2 (MAC) filtering L3 (IP) / L4 (Port) filtering	
	MAX clients per radio Internet freeze per SSID / user	
	Session control	
	Random MAC Detection	1



	Wireless (singlehop / multihop)
Meshing	Wired
WDS	Point to Point
	Point to MultiPoint
	DTIM interval
	OFDM Only (Disables 802.11b)
	BSS Rate and management rate
Radio Management	UAPSD (Power save)
	Inactivity timeout
	Radio mode control
	RTS/CTS Threshold
	IEEE 802.11d/h (DFS) support
	LLDP discovery, SFlow
Network Management	Proxy ARP
3	DHCP options 43, 60 and 82
	Port forwarding in router mode
	WLAN scheduling
Administration	Internet speed test
	Schedule reboot
	CoA (Change of Authorization)
Radius Integration	MAC Authentication
J	Dynamic VLAN
	Target wake time
	BSS colouring
Wi-Fi6 Features	Spatial reuse
	Orthogonal frequency division multiple access (OFDMA)
	Preamble puncturing
	Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
	Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit
	antennas
Advance Features	Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz
	Space-time block coding (STBC) for increased range and improved reception
	Low-density parity check (LDPC) for high-efficiency error correction and increased
	Transmit beam-forming (TxBF) for increased signal reliability and range
HawkEye - Rogue/WIDS	
Hawkeye Rogue/WIDS	Rogue SSID
Rogue AP	MAC Spoofing
	SSID Spoofing
	Honeypot / Evil twin attack
	Null Probe request attack
	Train 1 1000 1 equest attack



	RTS/CTS Abuse attack	
	Auth attack	
	Assoc attack	
	Fata jack tool attack	
	Man in the Middle attack	
WIDS	DHCP snooping server detection	
	AP flood attack	
	Block ACK DoS attack	
	Power saves frame attack	
	Malformed frame-Auth/Assoc attack	
	Deauth attack, Disassoc attack	
WID 6 (14") - 6	Omerta attack	
WIDS/WIPS	Password guessing attack	
	Ad-Hoc connection	
	Dos attack	
NIPS	DDos attack	
	Port scanning	
Diagnostics		
Network Diagnostics	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, ARP scanner	
RF Diagnostics	PCAP capture, Spectrum Analysis, Spectrum Channel metric, Spectrum FFT Duty cycle, WiFi Analyzer, Airbender	
Networking		
Ethernet WAN	WAN (DHCP/Static/PPPoE)	
USB WAN	USB dongle (3G/4G), Mobile tethering (USB)	
Protocols	Static, RIP v2, OSPF v2	
Tunneling	GRE, IPSec, Wire guard, OVPN	
Multi WAN	Yes, Auto Failover	
DHCP Server	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy	
WAN Security	Ethernet / USB port block management	
PPP Interface	PPPoE, L2TP, L2TP with IPSec	
DNS	Static, Caching, Dynamic DNS	
NAT	Masquerade (SNAT), Port forwarding (DNAT)	
VLAN Support	802.1Q (1 per BSSID), Port-based (Tagged, untagged)	
IoT	Supported (With BLE)	
IGMP	IGMP v2, IGMP Snooping	
Supported Features	Safe Search, ALG Control	
Supported reatures		



Quality of Service				
Auto QoS, 802.11e,	Auto QoS, 802.11e,			
Manual QoS (DSCP based	d, Voice, Video, BE and BK))		
WMM, 802.1p				
WiFi Calling				
DiffServ				
DSCP Tagging				
Performance & Capacit	у			
Dook DIIV Dotos	5 GHz	1201 Mbps (802.11ax)		
Peak PHY Rates	2.4 GHz	573.5 Mbps (802.11ax)		
Client Capacity	Up to 512 clients per acce	ess point		
SSID	Up to 32 per access point	t (16 per Radio)		
RF				
Maximum Aggregate	5 GHz	24 dBm		
Transmit Power (Adjusted as per	2.4.011-	27 40		
country regulations)	2.4 GHz	27 dBm		
Antenna Type		Built-in integrated antenna for both radios and BLE		
	5 GHz	6 dBi		
Antenna Gain (Max)	2.4 GHz	5 dBi		
	BLE	4.6 dBi		
EIRP (Adjusted as per	5 GHz	30 dBm		
country regulations)	2.4 GHz	32 dBm		
Power				
Rating	802.3 af PoE / at PoE+ (Class 4) (Fully functional with all components)			
Rating	12V DC 2A - Fully functional with all components			
Physical Interfaces	QN-I-270		QN-I-270-FR	
	WAN: 1 x 10/100/1000/2.		WAN: 1 x 10/100/1000 Base-T Ethernet,	
	Ethernet, Auto MDIX, RJ- PoE port	J-45 with 802.3at Auto-MDIX, RJ-45 with 802.3at PoE		
Ethernet	LAN: 2 x 10/100/1000 Ba	ase-T Ethernet.		
	Auto MDIX, RJ45 Console: 1 x RJ-45 LAN: 3 x 10/100/1000 Base-T Ethernet 802.3bz specifications, 802.3az Energy Efficient Ethernet (EEE)		LAN: 3 x 10/100/1000 Base-T Ethernet	
			, , ,	
Optical port			WAN: 1 x 1000 Base-X (SX / LX) SFP port	
Console	1x RJ-45 Ethernet			
USB	1x USB 3.0			
Buttons	Restart/Reset			
Kensington Security Slot	Available			
LED indicators	2.4 GHz, 5 GHz, Power			
	, , , , , , , , , , , , , , , , , , , ,			



Management		
	Standalone, Local (Web UI), SSH (CLI)	
Device Management	Quantum Rudder (Controller based)	
	Quantum Rudder (On-premises VM)	
	Quantum Rudder appliances (RR-200, RR-300, RR400)	
	Through NMS using SNMP MIBs	
	Local device web management	
Device /System Monitoring	SNMP v1, v2c, v3, Syslog	
NTP Server Configuration	Supported	
	Application Statistics	
Traffic Monitoring	IPDR Logs (IPFix , Netflow v9)	
	URL Logs (Syslog)	
Controller DR (Disaster Recovery)	Supported	
Device Security		
Certificate	Locally-significant certificates using PKI	
Controller Communication	Encrypted	
Port Access	802.1x RADIUS supplicant	
Application Integration		
PM WANI,		
NMS Integration - ZABBI	X, PRTG Monitor, Open NMS	
Environmental		
Operating Temperature	0°C (32°F) to 50°C (122°F)	
Humidity	Up to 95%, non-condensing	
Standard	Plenum-rated (UL2043)	
Physical		
Dimensions	19.5 cm x 19.5 cm x 3.9 cm	
Weight	0.65 kg (1.44 lbs)	
Mounting Kit	Suspended ceiling mount, Ceiling mount, Wall mount	
Firmware Management		
Cloud-managed firmware	update	
Scheduled firmware and security update		
Firmware upgrade via Acc	tess Point local GUI	



Certification and Compliances		
Certifications	Parameter	Standards
Regulatory (USA)	FCC	
	BIS	
	IEC-60215	
Regulatory (IN)	MTCTE (ER)	EMI/EMC (IEC / EN-61000* & CISPR 32), Safety (IS-13252 & IEC-60950), Radio, Technical (IPv4 & IPv6)
	IPv6 Ready	
	ETA (WPC)	NABL 2.4, NABL 5
Environmental Compliances	CE, RoHS	
Industry Association	Wi-Fi Alliance – WI-Fi6 Certified	
Dry Heat, Cold, Thermal Cyclic, Damp Heat	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30	

ORDERING INFORMATION

Part Code	Description
QN-I-270	Quantum Networks QN-I-270 dual-band 802.11ax indoor wireless access point, 2x2:2 streams, 1x1/2.5G base-T Ethernet port and 2x1G Base-T Ethernet ports, onboard BLE support, 802.3 at PoE support. Includes 3-year limited liability manufacturer's warranty for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
QN-I-270-FR	The Quantum Networks QN-I-270-FR is a dual-band 802.11ax indoor wireless access point with 2x2:2 streams, featuring a 1 x 10/100/1000/2.5G Base-T PoE Ethernet port, 3x1G Base-T Ethernet port, a 1x1000 Base-X (SX / LX) SFP port. It supports 802.3at PoE. The access point comes with a 3-year limited liability manufacturer's warranty. PoE injector, power adapter, and cloud controller license are not included.
QN-I-270-L-SD	License to activate SD-WAN functionality in the Access Point.