

# INDOOR ACCESS POINT

## QN-I-280



Up to 3 Gbps  
Data Rate



2.5 GbE  
Connectivity



2.4 GHz - 2x2,  
5 GHz - 2x2



MU-MIMO  
With OFDMA



3 Years  
Warranty

## PRODUCT OVERVIEW

QN-I-280 is a Wi-Fi 6 access point offering high-performance connectivity for any organization experiencing largely growing numbers of IoT and mobility requirements. With a maximum real-world data rate of up to 3 Gbps, it delivers high-speed, secure, reliable and seamless performance for any enterprise environment.

QN-I-280 provides concurrent dual-band 802.11ax wireless networking solutions. OFDMA technology offers highly efficient fast speed, awesome coverage and smooth performance in high-density areas like railway stations, hospitals, malls, public places, universities etc. It is managed by Quantum Rudder.

Quickly deploy futuristic customer engagement solutions using BLE Beacon.

Each access point comes with a three-year limited-liability manufacturer's warranty from the date of activation and theft prevention functionality to protect assets from misuse.

## KEY FEATURES

### Packed with the latest 802.11ax technology

QN-I-280 has all the advantages of a high-efficiency supported 11ax Access Point. It supports Wi-Fi 6 features such as OFDMA, Target Wake Time, and BSS coloring and spatial reuse.

### Phenomenal Wi-Fi performance

It is engineered for phenomenal Wi-Fi performance even in high-density environments for demanding voice and video applications. Provides improved coverage, increased capacity and seamless performance in dense environments.

### Build next-generation guest Wi-Fi networks

Deploy next-generation customer service hotspots with an integrated splash portal and BLE Beacons.

### Theft prevention functionality

Access Point is locked for deployment in any other network until decommissioned from the existing network.

### Three-year warranty

Three-year limited liability manufacturer's warranty from the date of activation of the device.

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax
	2.4 GHz	IEEE 802.11b/g/n/ax
Operating Mode	Access point, Router, Mesh mode	
Networking Mode	IPv4, IPv6, IPv4v6 (Dual stack), Gateway mode(NAT), Bridge mode	
Maximum Data Rates	5 GHz	802.11ax@ 160 MHz:2400 Mbps
		802.11ax@ 80 MHz:1201 Mbps
		802.11ax@ 40 MHz: 600 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11ac@ 80 MHz: 1083.3 Mbps
		802.11ac@ 40 MHz: 500 Mbps
		802.11ac@ 20 MHz: 240.5 Mbps
	2.4 GHz	802.11ax@ 40 MHz: 600 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11n@ 40 MHz: 500 Mbps
		802.11a/g@ 20 MHz: 54 Mbps
		802.11b@ 20 MHz: 11 Mbps
Maximum Receiver Sensitivity	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Supported Channels	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
		Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
Channel Bands	5 GHz	5.15-5.25 GHz (U-NII-1), 5.25-5.35 GHz (U-NII-2A), 5.47-5.725 GHz (U-NII-2C), 5.725-5.85 GHz (U-NII-3) (As per country regulations)
	2.4 GHz	2.4-2.484GHz (ISM) (As per country regulations)
Modulation Schemes	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11b	BPSK, QPSK, CCK
Radio Chains and Spatial Streams	2x2:2	Streams in 5GHz-OFDMA with MU-MIMO
	2x2:2	Streams in 2.4GHz- OFDMA with MU-MIMO
Channel Size	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80 (VHT) MHz
	802.11ax	20/40/80/160 (HE) MHz
Wireless Security	WPA3-AES personal, Enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed- AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	

	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	
<b>Wireless Security</b>	WEP-64, WEP-128,	
	802.11 w MFP (Management Frame Protection)	
	MAC based authentication	
	Captive portal-based authentication	
	802.11i	
	Quantum Secure	
	Hide SSID in beacons	
<b>External DB Support</b>	Radius, Active directory, LDAP, TACACS+	
<b>Web Authentication</b>	QN-Secure+, RADIUS, Active directory, LDAP	
<b>User Authentication</b>	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
	Directory	QIM, Microsoft active directory, LDAP, G suite, Oauth
	Mode	Via Controller /Access points
<b>Roaming</b>	IEEE 802.11k (Assisted Roaming)	
	IEEE 802.11v (BSS Transition Management)	
	IEEE 802.11r (Fast BSS Transition (FT))	
	Pairwise Master Key (PMK) caching	
	Opportunistic key caching	
	Seamless roaming for captive portal users	
<b>Channel / Tx Power Management</b>	Auto / Manual channel selection	
	Speedy channel for RF optimization	
	Channel switch for RF optimization	
	ATP-Automatic Transmit Power management	
<b>Client Management</b>	Band steering	
	Band balancing	
	Airtime fairness	
<b>Guest Management</b>	WISPr – Captive portal, HotSpot 2.0	
<b>Native Guest Portal</b>	Customized Template	Yes (User define, Theme based)
	Authentication Method	Click-through, Access code, Self-sign-up (SMS, Email), Sponsor based (Domain-based, Individual Email ID based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota based
<b>Access Control List</b>	Force DHCP	
	URL & Application filtering /Whitelisting	
	Full Client Isolation, Deny inter-user bridging, Deny intra-VLAN traffic	
	Bandwidth Restriction per SSID/User	
	OS restriction	
	L2 (MAC) filtering	
	L3 (IP) / L4 (Port) filtering	
	MAX clients per radio	
	Internet freeze per SSID/User	
	Session control	

	Random MAC Detection
<b>Meshing</b>	Wireless (singlehop / multihop)
	Wired
<b>WDS</b>	Point to Point
	Point to MultiPoint
<b>Radio Management</b>	DTIM interval
	OFDM Only (Disables 802.11b)
	BSS Rate and management rate
	UAPSD (Power save), Inactivity timeout
	Radio mode control, RTS/CTS Threshold
<b>Network Management</b>	IEEE 802.11d/h (DFS) support
	LLDP discovery, SFlow
	Proxy ARP
	DHCP options 43, 60 and 82
	Port forwarding in router mode
<b>Administration</b>	WLAN scheduling
	Internet speed test
	Schedule reboot
<b>Radius Integration</b>	CoA (Change of Authorization)
	MAC Authentication
	Dynamic VLAN
<b>Wi-Fi 6 Features</b>	Target wake time
	BSS coloring
	Spatial reuse
	Orthogonal frequency division multiple access (OFDMA)
	Preamble puncturing
<b>Advance Features</b>	Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
	Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas
	Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz
	Space-time block coding (STBC) for increased range and improved reception
	Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
	Transmit beam-forming (TxBF) for increased signal reliability and range
<b>HawkEye – Rogue/WIDS / WIPS / NIPS</b>	
<b>Rogue AP</b>	Rogue SSID
	MAC Spoofing
	SSID Spoofing
	Honeypot / Evil twin attack
	Null Probe request attack

<b>WIDS</b>	RTS/CTS Abuse attack
	Auth attack
	Assoc attack
	Fata jack tool attack
	Man in the Middle attack
	DHCP snooping server detection
	AP flood attack
	Block ACK DoS attack
	Power saves frame attack
	Malformed frame-Auth/Assoc attack
<b>WIDS/WIPS</b>	Deauth attack, Disassoc attack
	Omerta attack
	Password guessing attack
	Ad-Hoc connection
<b>NIPS</b>	Dos attack
	DDos attack
	Port scanning
<b>Diagnostics</b>	
<b>Network Diagnostics</b>	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, ARP scanner
<b>RF Diagnostics</b>	PCAP capture, Airbender
<b>Networking</b>	
<b>Ethernet WAN</b>	WAN (DHCP/Static/PPPoE)
<b>USB WAN</b>	USB dongle (3G/4G), Mobile tethering (USB)
<b>Protocols</b>	Static, RIP v2, OSPF v2
<b>Tunneling</b>	GRE, IPSec, Wire guard, OVPN
<b>Multi-WAN</b>	Yes, Auto-Failover
<b>DHCP Server</b>	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy
<b>WAN Security</b>	Ethernet / USB port block management
<b>PPP Interface</b>	PPPoE, L2TP, L2TP with IPSec
<b>DNS</b>	Static, Caching, Dynamic DNS
<b>NAT</b>	Masquerade (SNAT), Port forwarding (DNAT)
<b>VLAN Support</b>	802.1Q (1 per BSSID), Port-based (Tagged, untagged), IoT Capable
<b>IGMP</b>	IGMP v2, IGMP Snooping
<b>Supported Features</b>	Safe Search, ALG Control
	UPnP, DMZ Host, Adblock

Quality of Service			
Auto QoS, 802.11e,			
Manual QoS (DSCP based, Voice, Video, BE and BK)			
WMM, 802.1p			
WiFi Calling			
DiffServ			
DSCP Tagging			
Performance & Capacity			
Peak PHY Rates	5 GHz	2400 Mbps (802.11ax)	
	2.4 GHz	600 Mbps (802.11ax)	
Client Capacity	Up to 512 clients per access point		
SSID	Up to 32 per access point (16 per Radio)		
RF			
Maximum Aggregate Transmit Power (Adjusted as per country regulations)	5 GHz	26 dBm	
	2.4 GHz	27 dBm	
Antenna Type	Built-in integrated antenna for both radios and BLE		
Antenna Gain (Max)	5 GHz	6 dBi	
	2.4 GHz	6 dBi	
	BLE	5 dBi	
EIRP (Adjusted as per country regulations)	5 GHz	32 dBm	
	2.4 GHz	33 dBm	
Power			
Rating	802.3 af PoE / at PoE+ (Class 4) (Fully functional with all components)		
	12V DC 2A Type C - Fully functional with all components		
Physical Interfaces	QN-I-280	QN-I-280-IoT	QN-I-280-FR
Ethernet ports	WAN: 1 x 10/100/1000/2.5G N Base -T Ethernet, Auto-MDIX, RJ-45 with 802.3at PoE port	WAN: 1 x 10/100/1000/2.5G N Base -T Ethernet, Auto-MDIX, RJ-45 with 802.3at PoE port	WAN: 1 x 10/100/1000 Base -T Ethernet, Auto-MDIX, RJ-45 with 802.3at PoE port
	LAN:1 x 1G Base-T Ethernet	LAN:1 x 1G Base-T Ethernet with PoE out	LAN: 3 x 1G Base-T Ethernet
	802.3bz specifications, 802.3az Energy Efficient Ethernet (EEE)		
Optical port	----	----	WAN: 1 x 1000 Base-X (SX / LX) SFP port
IoT	No	Yes (Bluetooth/Zigbee/Thread)	No
USB /Console	----	1	----
Buttons	Restart/Reset		

<b>Kensington security slot</b>	Available
<b>LED indicators</b>	Power, 2.4 GHz, 5 GHz, Standalone/Cloud
<b>Management</b>	
<b>Device Management</b>	Standalone, Local (web UI), SSH (CLI)
	Quantum Rudder (Controller based)
	Quantum Rudder (On-premises VM)
	Quantum Rudder appliances (RR-200, RR-300, RR400)
	Through NMS using SNMP MIBs
	Local device web management
<b>Device /System monitoring</b>	SNMP v1, v2c, v3, Syslog
<b>NTP Server Configuration</b>	Supported
<b>Traffic Monitoring</b>	Application Statistics
	URL Logs (Syslog)
<b>Controller DR (Disaster Recovery)</b>	Supported
<b>Device Security</b>	
<b>Certificate</b>	Locally-significant certificates using PKI
<b>Controller Communication</b>	Encrypted
<b>Port Access</b>	802.1x RADIUS supplicant
<b>Application Integration</b>	
PM WANI	
NMS Integration - ZABBIX, PRTG Monitor, Open NMS	
<b>Environmental</b>	
<b>Operating Temperature</b>	0°C (32°F) to 55°C (131°F)
<b>Humidity</b>	Up to 95%, non-condensing
<b>Standard</b>	Plenum-rated (UL2043)
<b>Physical</b>	
<b>Dimensions</b>	19.5 cm x 19.5 cm x 3.9 cm
<b>Weight</b>	0.65 kg (1.44 lbs)
<b>Mounting Kit</b>	Suspended ceiling mount, Ceiling mount, Wall mount
<b>Certifications</b>	
<b>Regulatory</b>	FCC
<b>Standard</b>	IEC-60950
<b>Environmental</b>	CE
	RoHS
<b>Firmware Management</b>	
Cloud-managed firmware update	
Scheduled firmware and security update	
Firmware upgrade via Access Point local GUI	

Certification and Compliances		
Certifications	Parameter	Standards
Regulatory (USA)	FCC	
Regulatory (IN)	BIS	
	IPv6 Ready	
	ETA (WPC)	NABL 2.4, NABL 5

## ORDERING INFORMATION

Part Code	Description
<b>QN-I-280</b>	Quantum Networks QN-I-280 dual-band 802.11ax indoor wireless access point, 2x2:2 streams, 1x1/2.5G PoE N Base-T Ethernet port and 1x1G Base-T Ethernet ports, 802.3 at PoE support. includes 3-year limited liability manufacturer's warranty for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
<b>QN-I-280-IoT</b>	The Quantum Networks QN-I-280-IoT is a dual-band 802.11ax indoor wireless access point with 2x2:2 streams, featuring a 1x1/2.5G PoE N Base-T Ethernet port, a 1x1G Base-T Ethernet port, and a 1xUSB/Console port. It supports 802.3at PoE, Bluetooth, Zigbee, and Thread. The access point comes with a 3-year limited liability manufacturer's warranty. PoE injector, power adapter, and cloud controller license are not included.
<b>QN-I-280-FR</b>	The Quantum Networks QN-I-280-FR is a dual-band 802.11ax indoor wireless access point with 2x2:2 streams, featuring a 1x1G Base-T PoE Ethernet port, a 3x1G Base-T Ethernet port, a 1x1000 Base-X (SX / LX) SFP port. It supports 802.3at PoE. The access point comes with a 3-year limited liability manufacturer's warranty. PoE injector, power adapter, and cloud controller license are not included.