

OUTDOOR ACCESS POINT

QN-O-240



PRODUCT OVERVIEW

QN-O-240 built-in with a smart antenna and MU-MIMO technology provides high data-rates even in high-density and high-interference environments.

QN-O-240 provides concurrent dual-band, 802.11ax wireless networking solutions. OFDMA technology provides highly efficient fast speed, awesome coverage and smooth performance in high-density areas like railway stations, hospitals, malls, public places, universities etc.

QN-O-240 is manageable through a centralized platform and supported by Quantum Rudder. QN-O-240 can also be deployed as a standalone Access Point.

Each Access Point comes with a one-year limited liability manufacturer's warranty from the date of activation and theft prevention functionality to protect assets from misuse.



Up to 3 Gbps
Data Rate



2.5 GbE
Connectivity



2.4 GHz - 2x2,
5 GHz - 2x2



MU-MIMO
With OFDMA



1 Year
Warranty

KEY FEATURES

Delivering high-performance outdoor Wi-Fi access.

Deploy secure and reliable outdoor hotspots at Transportation hubs, Stadiums, Smart cities and Rural Wi-Fi setups.

Phenomenal Wi-Fi performance.

Engineered for phenomenal Wi-Fi performance even in high-density environments for demanding voice and video applications. Provides improved coverage, increased capacity and seamless performance in dense environments.

Cost-Efficient Connectivity.

Reduces operational costs and the expense of additional hardware required for deployment by service providers/telcos. SFP port provides high-speed fiber backhaul without any additional hardware.

Theft prevention functionality.

Access Point is locked for deployment in any other network until decommissioned from the existing network.

Industrial-grade IP67 enclosure.

IP67 rating can withstand challenging environments with extreme temperatures and dusty environments.

Easy to manage.

Easily manage Wi-Fi infrastructure through the feature-rich Quantum Rudder management console.

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax
	2.4 GHz	IEEE 802.11b/g/n/ax
Operating Mode	Access point, Router, Mesh mode	
Networking Mode	IPv4, IPv6, IPv4v6 (Dual stack), Gateway mode (NAT), Bridge mode	
Maximum Data Rates	5 GHz	802.11ax@ 160 MHz: 2400 Mbps
		802.11ax@ 80 MHz: 1201 Mbps
		802.11ax@ 40 MHz: 600 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11ac@ 80 MHz: 1083.3 Mbps
		802.11ac@ 40 MHz: 500 Mbps
		802.11ac@ 20 MHz: 240.5 Mbps
	2.4 GHz	802.11ax@ 40 MHz: 600 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11n@ 40 MHz: 500 Mbps
		802.11a/g@ 20 MHz: 54 Mbps
		802.11b@ 20 MHz: 11 Mbps
Maximum Receiver Sensitivity	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Supported Channels	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
		Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
Channel Bands	5 GHz	5.15-5.25 GHz (U-NII-1), 5.25-5.35 GHz (U-NII-2A), 5.47-5.725 GHz (U-NII-2C), 5.725-5.85 GHz (U-NII-3) (As per country regulations)
	2.4 GHz	2.4-2.484GHz (ISM) (As per country regulations)
Modulation Schemes	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11b	BPSK, QPSK, CCK
Radio Chains and Spatial Streams	2x2:2	Streams in 5GHz-OFDMA with MU-MIMO
	2x2:2	Streams in 2.4GHz- OFDMA with MU-MIMO
Channel Size	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80 (VHT) MHz
	802.11ax	20/40/80/160 (HE) MHz
Wireless Security	WPA3-AES personal, enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed- AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	

	WEP-64, WEP-128	
	802.11 w MFP (Management Frame Protection)	
	MAC based authentication, Captive portal-based authentication	
	802.11i, Quantum Secure	
	Hide SSID in beacons	
External DB Support	Radius, Active directory, LDAP, TACACS+	
Web Authentication	QN-Secure+, RADIUS, Active directory, LDAP	
User Authentication	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
	Directory	QIM, Microsoft active directory, LDAP, G suite, OAuth
	Mode	Via Controller / Access points
Roaming	IEEE 802.11k (Assisted Roaming)	
	IEEE 802.11v (BSS Transition Management)	
	IEEE 802.11r (Fast BSS Transition (FT))	
	Pairwise Master Key (PMK) caching	
	Opportunistic key caching	
	Seamless roaming for captive portal users	
Channel / Tx Power Management	Auto / Manual channel selection	
	Speedy channel for performance optimization	
	Channel switch for performance optimization	
	ATP-Automatic Transmit Power management	
Client Management	Band steering	
	Band balancing	
	Airtime fairness	
Guest Management	WISPr – Captive portal, HotSpot 2.0	
Native Guest Portal	Customized Template	Yes (User define, Theme-based)
	Authentication Method	Click-through, Access code, Self-sign-up (SMS, Email), Sponsor based (Domain-based, Individual Email ID based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota based
Access Control List	Force DHCP	
	URL & Application filtering /Whitelisting	
	Full Client Isolation, Deny inter-user bridging, Deny intra-VLAN traffic	
	Bandwidth Restriction per SSID/User	
	OS restriction	
	L2 (MAC) filtering	
	L3 (IP) / L4 (Port) filtering	
	MAX clients per radio	
	Internet freeze per SSID/user	
	Session control	
	Random MAC Detection	

Meshing	Wireless (singlehop / multihop) Wired
WDS	Point to Point Point to MultiPoint
Radio Management	DTIM interval OFDM Only (Disables 802.11b) BSS Rate and management rate UAPSD (Power save) Inactivity timeout Radio mode control RTS/CTS Threshold
Network Management	IEEE 802.11d/h (DFS) support LLDP discovery, SFlow Proxy ARP DHCP options 43, 60 and 82 Port forwarding in router mode
Radius Integration	CoA (Change of Authorization) MAC Authentication Dynamic VLAN
Administration	WLAN scheduling Internet speed test Schedule reboot
Wi-Fi 6 Features	Target wake time BSS colouring Spatial reuse Orthogonal frequency division multiple access (OFDMA) Preamble puncturing
Advance Features	Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz Space-time block coding (STBC) for increased range and improved reception Low-density parity check (LDPC) for high-efficiency error correction and increased throughput Transmit beam-forming (TxBF) for increased signal reliability and range
HawkEye - Rogue/WIDS / WIPS / NIPS	
Rogue AP	Rogue SSID MAC Spoofing

Rogue AP	SSID Spoofing
	Honeypot / Evil twin attack
	Null Probe request attack
WIDS	RTS/CTS Abuse attack
	Auth attack
	Assoc attack
	Fata jack tool attack
	Man in the Middle attack
	DHCP snooping server detection
	AP flood attack
	Block ACK DoS attack
	Power saves frame attack
	Malformed frame-Auth/Assoc attack
WIDS/WIPS	Deauth attack
	Disassoc attack
	Omerta attack
	Password guessing attack
	Ad-Hoc connection
NIPS	Dos attack
	DDos attack
	Port scanning
Diagnostics	
Network Diagnostics	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, ARP scanner
RF Diagnostics	PCAP capture, Spectrum Analysis, Spectrum Channel metric, Spectrum FFT Duty cycle, WiFi Analyzer, Airbender
Networking	
Ethernet WAN	WAN (DHCP/Static/PPPoE)
Protocols	Static, RIP v2, OSPF v2
Tunneling	GRE, IPSec, Wire guard, OVPN
Multi- WAN	Yes, Auto-Failover
DHCP Server	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy
WAN Security	Ethernet port block management
PPP Interface	PPPoE, L2TP, L2TP with IPSec
DNS	Static, Caching, Dynamic DNS
NAT	Masquerade (SNAT), Port forwarding (DNAT)
VLAN Support	802.1Q (1 per BSSID or dynamic per user-based on RADIUS), Port-based (Tagged, untagged)
IGMP	IGMP v2, IGMP Snooping
Supported Features	Safe Search, ALG Control
	UPnP, DMZ Host, Adblock

Quality of Service										
Auto-QoS, 802.11e,										
Manual QoS (DSCP based, Voice, Video, BE and BK)										
WMM, 802.1p										
WiFi Calling										
DiffServ										
Performance & Capacity										
Peak PHY Rates	5 GHz		2400 Mbps (802.11ax)							
	2.4 GHz		600 Mbps (802.11ax)							
Client Capacity	Up to 512 clients per Access point									
SSID	Up to 16 per access point (8 per Radio)									
RF		QN-O-240	QN-O-240-N							
Maximum Aggregate Transmit Power (As per country regulations)	5 GHz	26 dBm	26 dBm	24 dBm	24 dBm	24 dBm				
	2.4 GHz	27 dBm	27 dBm	25 dBm	25 dBm	25 dBm				
Antenna Gain (Max)	5 GHz	6 dBi	5 dBi	8 dBi	12 dBi	15 dBi				
	2.4 GHz	6 dBi	5 dBi	8 dBi	12 dBi	15 dBi				
EIRP (As per country regulations)	5 GHz	32 dBm	31 dBm	32 dBm	36 dBm	39 dBm				
	2.4 GHz	33 dBm	32 dBm	33 dBm	37 dBm	40 dBm				
Antenna Type		Built-in integrated antenna for both radios	External antennas connectors							
Power										
Rating	802.3 af PoE / at PoE+ (Class 4) (Fully functional with all components)									
Physical Interfaces										
Ethernet	WAN/LAN: 1x 10/100/1000/2.5G N Base-T Ethernet, Auto-MDIX, RJ-45 with 802.3at PoE									
	802.3bz specifications, 802.3az Energy Efficient Ethernet (EEE)									
Fiber	WAN/LAN: 1x 1G Base-X (SX / LX) SFP port									
Buttons	Restart/Reset									
LED Indicators	Power, 2.4 GHz, 5 GHz, Uplink									
Management										
Device Management	Standalone, Local (web UI), SSH (CLI)									
	Quantum Rudder (Controller based)									
	Quantum Rudder (On-premises VM)									
	Quantum Rudder appliances (RR-200, RR-300, RR400)									
	Through NMS using SNMP MIBs									
	Local device web management									

Device /System Monitoring	SNMP v1, v2c, v3, Syslog	
NTP Server Configuration	Supported	
Traffic Monitoring	Application Statistics IPDR Logs (IPFix , Netflow v9)	
Controller DR (Disaster Recovery)	Supported	
Device Security		
Certificate	Locally-significant certificates using PKI	
Controller Communication	Encrypted	
Port Access	802.1x RADIUS supplicant	
Application Integration		
PM WANI,		
NMS Integration - ZABBIX, PRTG Monitor, Open NMS		
Environmental		
Operating temperature	-40°C (-40F) ~ +70°C (+158F)	
Humidity	5% ~ 100% non-condensing	
Wind Resistance	160 kmph for sustained wind, 250 kmph for wind gusts	
Standard	IP67	
Physical		
Dimensions	23.9cm(L), 19.5cm(W), 8.3cm(H)	
Weight	1575 g (3.47 lbs)	
Mounting kit	Pole mount	
Firmware Management		
Cloud-managed firmware update		
Scheduled firmware and security update		
Firmware upgrade via Access Point local GUI		
Certification and Compliances		
Certifications	Parameter	Standards
Regulatory (USA)	FCC	
Regulatory (IN)	BIS	IS-13252, IEC-60950
	MTCTE (ER)	MI/EMC (IEC / EN-61000* & CISPR 32), Safety (IS-13252 & IEC-60950), Radio, Technical (IPv4 & IPv6)
	IPv6 Ready	
Environmental Compliances	ETA (WPC)	NABL 2.4, NABL 5
	IEC-60215	
Environmental Compliances	CE, RoHS, IP67	

ORDERING INFORMATION

Part Code	Description
QN-O-240	Quantum Networks QN-O-240 dual-band 802.11ax outdoor wireless access point, 2x2:2 streams, 1x1/2.5G N Base-T Ethernet port and 1x1G base-X SFP port, 802.3 at PoE support. Includes 1-year limited liability manufacturer's warranty for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
QN-O-240-N	Quantum Networks QN-O-240-N connectorized dual-band 802.11ax outdoor wireless access point, 2x2:2 streams, 1x1/2.5G N Base-T Ethernet port and 1x1G base-X SFP port, 802.3 at PoE support. Includes 1-year limited liability manufacturer's warranty for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
QN-O-240-PE	Quantum Networks QN-O-240-PE dual-band 802.11ax outdoor wireless access point, 2x2:2 streams, 1x1/2.5G N Base-T Ethernet port and 1x1G Base-T Ethernet port, 802.3 at PoE support. Includes 1-year limited liability manufacturer's warranty for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
Accessories Part Code*	Description
QN-ANT-25-17DB	Dual Band (2.4GHZ & 5 GHZ) External outdoor antenna with N-Connector, Gain: 17DBI

DEVICE UPGRADE

Part Code	Description
QN-O-240-IoT	Additional BLE module for IoT-related applications.
QN-O-240-DPOE	Additional PoE support on the LAN interface.

*The antenna connection cable (N-Type) is not included in the device packaging and must be purchased separately, as per requirement.