

# OUTDOOR ACCESS POINT

## QN-O-710



**The QN-O-710 Next-Gen Outdoor Access Point** delivers high-speed, low-latency Wi-Fi in wide, high-traffic areas. Designed for modern outdoor connectivity, it's an ideal pick for campuses, smart cities, resorts, stadiums, and industrial zones. Whether it's enabling smooth guest access in hotel lawns, supporting remote learning outdoors, or powering surveillance networks, the QN-O-710 is built for consistently reliable performance.

## PRODUCT OVERVIEW



Up to 3.5 Gbps  
Data Rate



2.5 GbE  
Connectivity



2.4 GHz - 2x2,  
5 GHz - 2x2



MU-MIMO  
With OFDMA



1 Year  
Warranty

**Powered by Wi-Fi 7 with dual-band 2x2:2 MU-MIMO**, the QN-O-710 supports advanced features like Multi-Link Operation (MLO), enabling simultaneous data transmission across both 2.4 GHz and 5 GHz bands. This ensures efficient client distribution and spectrum utilization, especially in dense environments. Integrated HawkEye security further empowers the system by actively detecting and mitigating wireless threats to maintain a secure network environment.

**With support for 160 MHz channel width, OFDMA, and 4096-QAM**, the QN-O-710 delivers exceptional data throughput and reduced latency, even across large open spaces. Its robust outdoor design ensures uniform wireless coverage in public areas and facility exteriors while simplifying large-scale deployments without compromising on performance or reliability.

## KEY FEATURES

### Wi-Fi 7 Outdoor Optimization

Built on 802.11be (Wi-Fi 7) with 160 MHz channels, 4096-QAM, and MLO to deliver ultra-fast, low-latency wireless in large outdoor spaces.

### Dual-Band 2x2:2 MU-MIMO Architecture

Supports multiple users concurrently on both 2.4 GHz and 5 GHz, ensuring stable and efficient connectivity in high-density, open-air environments.

### HawkEye Wireless Security Suite

Protects the network by detecting and mitigating rogue APs, spoofing attacks, deauthentication floods, DoS threats, and port scans in real time.

### Seamless Centralized Management

Integrates with Quantum Rudder for unified cloud or on-premise control, featuring zero-touch provisioning and firmware updates for streamlined deployment.

### Scalable for Multi-Site Outdoor Networks

Ideal for stadiums, campuses, smart cities, and industrial sites—designed to simplify and secure outdoor network rollouts at scale.

## KEY SPECIFICATIONS

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax/be
	2.4 GHz	IEEE 802.11b/g/n/ax/be
Operating Mode	Access point, Router, Mesh mode	
Networking Mode	IPv4, IPv6, IPv4v6 (Dual-stack), Gateway mode (NAT), Bridge mode	
Maximum Data Rates	5 GHz	802.11be@ 160 MHz: 2882 Mbps
		802.11be@ 80 MHz: 1441 Mbps
		802.11be@ 40 MHz: 688 Mbps
		802.11ax@ 160 MHz: 2402 Mbps
		802.11ax@ 80 MHz: 1201 Mbps
		802.11ax@ 40 MHz: 573.5 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11ac@ 80 MHz: 1083.3 Mbps
		802.11ac@ 40 MHz: 500 Mbps
		802.11ac@ 20 MHz: 240.5 Mbps
Maximum Receiver Sensitivity	2.4 GHz	802.11be@ 40 MHz: 688 Mbps
		802.11be@ 20 MHz: 344 Mbps
		802.11ax@ 40 MHz: 573.5 Mbps
		802.11ax@ 20 MHz: 286.8 Mbps
		802.11n@ 40 MHz: 500 Mbps
		802.11b/g@ 20 MHz: 54 Mbps
		802.11b@ 20 MHz: 11 Mbps
Supported Channels	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Modulation Schemes	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
	Dynamic frequency selection (DFS) optimizes the use of available RF spectrum	
Channel Bands	5 GHz	5.15-5.25 GHz (U-NII-1), 5.25-5.35 GHz (U-NII-2A), 5.47-5.725 GHz (U-NII-2C), 5.725-5.85 GHz (U-NII-3) (as per country regulations)
	2.4 GHz	2.4-2.484GHz (ISM) (as per country regulations)
Radio Chains and Spatial Streams	802.11be	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM, 4096-QAM
	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM, 4096-QAM
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11n	BPSK, QPSK, 16-QAM, 64-QAM, 1024-QAM, 4096-QAM
	802.11b/g	BPSK, QPSK, CCK
Streams	2x2:2	Streams in 5GHz-OFDMA (802.11ax) and OFDM (802.11ac) with MU-MIMO
	2x2:2	Streams in 2.4GHz- OFDM (802.11a/g/n) and DSSS (802.11b) with MU-MIMO

<b>Channel Size</b>	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80 (VHT) MHz
	802.11ax	20/40/80/160 (HE) MHz
	802.11be	20/40/80/160 (EHT) MHz
<b>Wireless Security</b>	WPA3-AES personal, enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed- AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	
	WEP-64, WEP-128,	
	802.11 w MFP (Management Frame Protection)	
	MAC-based authentication	
	Captive portal-based authentication	
<b>External DB Support</b>	802.11i	
	Quantum Secure	
	Hide SSID in beacons	
	Radius, Active Directory, LDAP, TACACS+	
<b>Web Authentication</b>	QN-Secure+, RADIUS, Active Directory, LDAP	
<b>User Authentication</b>	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
	Directory	QIM, Microsoft Active Directory, LDAP, GSuite, Oauth
	Mode	Via Controller /Access points
<b>Roaming</b>	IEEE 802.11k (Assisted Roaming)	
	IEEE 802.11v (BSS Transition Management)	
	IEEE 802.11r (Fast BSS Transition (FT))	
	Pairwise Master Key (PMK) caching	
	Opportunistic key caching	
	Seamless roaming for captive portal users	
<b>Channel / Tx Power Management</b>	Auto / Manual channel selection	
	Speedy channel for RF optimization	
	Channel switch for RF optimization	
	ATP-Automatic Transmit Power management	
<b>Client Management</b>	Band steering	
	Band balancing	
	Airtime fairness	
<b>Guest Management</b>	WISPr – Captive portal, HotSpot 2.0	
<b>Native Guest Portal</b>	Customized Template	Yes (User-defined, Theme-based)
	Authentication Method	Click-through, Access code, Self-sign-up (SMS, Email), Sponsor-based (Domain-based, Individual Email ID-based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota-based

<b>Access Control List</b>	Force DHCP
	URL & Application filtering / Whitelisting
	Full Client Isolation, Deny inter-user bridging, Deny intra-VLAN traffic
	Bandwidth Restriction per SSID/per User
	OS restriction
	L2 (MAC) filtering
	L3 (IP) / L4 (Port) filtering
	MAX clients per radio
	Internet freeze per SSID / user
	Session control
	Random MAC Detection
<b>Meshing</b>	Wireless (singlehop / multihop)
	Wired
<b>WDS</b>	Point to Point
	Point to MultiPoint
<b>Radio Management</b>	DTIM interval
	OFDM Only (Disables 802.11b)
	BSS Rate and management rate
	UAPSD (Power save)
	Inactivity timeout
	Radio mode control
	RTS/CTS Threshold
<b>Network Management</b>	IEEE 802.11d/h (DFS) support
	LLDP discovery, SFlow
	Proxy ARP
	DHCP options 43, 60 and 82
	Port forwarding in router mode
<b>Administration</b>	WLAN scheduling
	Internet speed test
	Schedule reboot
<b>Radius Integration</b>	CoA (Change of Authorization)
	MAC Authentication
	Dynamic VLAN
<b>Wi-Fi7/6 Features</b>	Target wake time
	Multi-Link Operation
	BSS colouring
	Spatial reuse
	Orthogonal frequency division multiple access (OFDMA)
	Preamble puncturing

<b>Advance Features</b>	Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
	Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas
	Short guard interval for 20-MHz, 40-MHz, 80-MHz, 160-MHz and 360-MHz
	Space-time block coding (STBC) for increased range and improved reception
	Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
	Transmit beam-forming (TxBF) for increased signal reliability and range
<b>HawkEye – Rogue/WIDS / WIPS / NIPS</b>	
<b>Rogue AP</b>	Rogue SSID
	MAC Spoofing
	SSID Spoofing
	Honeypot / Evil twin attack
	Null Probe request attack
<b>WIDS</b>	RTS/CTS Abuse attack
	Auth attack
	Assoc attack
	Fata jack tool attack
	Man in the Middle attack
	DHCP snooping server detection
	AP flood attack
	Block ACK DoS attack
	Power saves frame attack
	Malformed frame-Auth/Assoc attack
<b>WIDS/WIPS</b>	Deauth attack
	Disassoc attack
	Omerta attack
	Password guessing attack
	Ad-Hoc connection
<b>NIPS</b>	Dos attack
	DDos attack
	Port scanning
<b>Diagnostics</b>	
<b>Network Diagnostics</b>	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, ARP scanner
<b>RF Diagnostics</b>	PCAP capture, Spectrum Analysis, Spectrum Channel metric, Spectrum FFT Duty cycle, WiFi Analyzer, Airbender

<b>Networking</b>												
<b>SFP/Ethernet WAN</b>	WAN (DHCP/Static/PPPoE)											
<b>Protocols</b>	Static, RIP v2, OSPF v2											
<b>Tunneling</b>	GRE, IPSec, Wire guard, OVPN											
<b>Multi WAN</b>	Yes, Auto Failover											
<b>DHCP Server</b>	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy											
<b>WAN Security</b>	Ethernet											
<b>PPP Interface</b>	PPPoE, L2TP, L2TP with IPSec											
<b>DNS</b>	Static, Caching, Dynamic DNS											
<b>NAT</b>	Masquerade (SNAT), Port forwarding (DNAT)											
<b>VLAN Support</b>	802.1Q (1 per BSSID), Port-based (Tagged, untagged)											
<b>IoT</b>	Supported											
<b>IGMP</b>	IGMP v2											
	IGMP Snooping											
<b>Supported Features</b>	Safe Search, ALG Control											
	UPNP, DMZ Host, Adblock											
<b>Quality of Service</b>												
Auto QoS, 802.11e,												
Manual QoS (DSCP based, Voice, Video, BE and BK)												
WMM, 802.1p												
WiFi Calling												
DiffServ												
DSCP Tagging												
<b>Performance &amp; Capacity</b>												
<b>Peak PHY Rates</b>	5 GHz	2882 Mbps (802.11be)										
	2.4 GHz	688 Mbps (802.11be)										
<b>Client Capacity</b>	Up to 512 clients per Access point											
<b>SSID</b>	Up to 32 per access point (16 per Radio)											
<b>RF</b>		<b>QN-O-710</b>	<b>QN-O-710-N</b>									
<b>Maximum Aggregate Transmit Power (Adjusted as per country regulations)</b>			QN-ANT-5-5DB/ QN-ANT-2-5DB	QN-ANT-5-8DB/ QN-ANT-2-8DB	QN-ANT-5-12DB/ QN-ANT-2-12DB	QN-ANT-5-15DB/ QN-ANT-2-15DB						
	5 GHz	25 dBm	25 dBm	23 dBm	23 dBm	23 dBm						
	2.4 GHz	26 dBm	26 dBm	24 dBm	24 dBm	24 dBm						
<b>Antenna Gain (Max)</b>	5 GHz	4 dBi	5 dBi	8 dBi	12 dBi	15 dBi						
	2.4 GHz	4 dBi	5 dBi	8 dBi	12 dBi	15 dBi						
<b>EIRP (Adjusted as per country regulations)</b>	5 GHz	30 dBm		31 dBm	35 dBm	38 dBm						
	2.4 GHz	31 dBm		32 dBm	36 dBm	39 dBm						
<b>Rating</b>	802.3 at PoE+ (Class 4) (Fully functional with all components)											
<b>Antenna Type</b>	Built-in integrated antenna for both radios.	External antenna connectors										

<b>Physical Interfaces</b>	
<b>Ethernet</b>	WAN: 1x 10/100/1000/2.5G N Base-T ethernet, Auto MDIX, RJ-45 with 802.3at 802.3bz specifications, 802.3az Energy Efficient Ethernet (EEE)
<b>Buttons</b>	Restart/Reset
<b>LED Indicators</b>	Power, 2.4 GHz, 5 GHz, Standalone/Cloud
<b>Management</b>	
<b>Device Management</b>	Standalone, Local (web UI), SSH (CLI)
	Quantum Rudder (Controller-based)
	Quantum Rudder (On-premises VM)
	Quantum Rudder appliances (RR-200, RR-300, RR400)
	Through NMS using SNMP MIBs
	Local device web management
<b>Device /System Monitoring</b>	SNMP v1, v2c, v3, Syslog
<b>NTP Server Configuration</b>	Supported
<b>Traffic Monitoring</b>	Application Statistics
	IPDR Logs (IPFix, Netflow v9)
	URL Logs (Syslog)
<b>Controller DR (Disaster Recovery)</b>	Supported
<b>Device Security</b>	
<b>Certificate</b>	Locally-significant certificates using PKI
<b>Controller Communication</b>	Encrypted
<b>Port Access</b>	802.1x RADIUS supplicant
<b>Application Integration</b>	
PM WANI,	
NMS Integration - ZABBIX, PRTG Monitor, Open NMS	
SIEM Integration- Splunk, IBM QRadar (Syslog format)	
<b>Environmental</b>	
<b>Operating Temperature</b>	-40°C (40°F) ~ to 70°C (+158°F)
<b>Humidity</b>	5% ~ 100% non-condensing
<b>Wind Resistance</b>	160 kmph for sustained wind, 250 kmph for wind gusts
<b>Standard</b>	IP67

<b>Physical</b>	
<b>Dimensions</b>	18.6 cm (L) x 18.6 cm (W) x 3.7 cm (H)
<b>Weight</b>	0.55 kg (1.21 lbs.)
<b>Mounting Kit</b>	Pole Mount
<b>Firmware Management</b>	
Cloud-managed firmware update	
Scheduled firmware and security update	
Firmware upgrade via Access Point local GUI	

## ORDERING INFORMATION

<b>Part Code</b>	<b>Description</b>
<b>QN-O-710</b>	The Quantum Networks QN-O-710 is a dual-band 802.11be outdoor wireless access point, supporting 2x2:2 streams on both 5 GHz and 2.4 GHz bands. It features a 1x2.5G N-Base-T Ethernet port with PoE support. Includes 1-year limited liability manufacturer's warranty start from date of activation for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
<b>QN-O-710-N</b>	The Quantum Networks QN-O-710-N connectorized dual-band 802.11be outdoor wireless access point, supporting 2x2:2 streams on both 5 GHz and 2.4 GHz bands. It features a 1x2.5G N-Base-T Ethernet port with PoE support. Includes 1-year limited liability manufacturer's warranty start from date of activation for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.
<b>Accessories Part Codes *</b>	<b>Description</b>
<b>QN-ANT-25-17DB</b>	Dual Band (2.4GHZ & 5 GHZ) External outdoor antenna with N-Connector, Gain: 17DBI

\*The antenna connection cable (N-Type) is not included in the device packaging and must be purchased separately, as per requirement.